# MICROSWITCHES FOR SQUARE BODY FUSES

## **Type T Microswitch**

Adler	Bussmann	Microswitch
Part Number	Part Number	Q/C.Lugs
MS000B	170H0236	6.3 x 0.8mm

Rating: 2A

Voltage: 250VAC Indication: One normally open (NO) and one normally closed (NC) contact. Suits Type T Indicator: DIN 43620, DIN 43653, Flush End, French and US Square Body fuses. Note: Type T Indicator; compatible with a Type T microswitch, requires a minimum of 20V to operate.




plate tag of the fuse. Flag Indicator

Type T microswitches

are fitted onto the cover

Aadler

Aadler



170H0236

Fuse shown with

# **MICROSWITCHES FOR SQUARE BODY FUSES**

## **Type K Microswitch**

Adler Part Number MS0003


Bussmann Microswitch Part Number Q/C.Lugs 170H0069 6.3 x 0.8mm

#### Rating: 2A

Voltage: 250VAC Indication: One normally open (NO) and one normally closed (NC) contact. Suits Type K Indicator: DIN 43653, Flush End, French and US Square Body fuses. Notes: As a matter of safety, the factory mounted adapter must not be removed from the fuse.

Type K Indicator; compatible with a Type K microswitch, requires a minimum of 1.5V to operate.

148



Depth: 16.8mm







**MS0003** 

Type K microswitches are fitted onto the black indicator body, which is part of the fuse.



Fuse shown with microswitch attached.

Email: sales@swe-check.com.au Phone: (+61) 03 9521 6133



microswitch attached.

### Bussmann



170H0069

Smaller Tab