

# MULTI-POLE FUSE LINKS (3-IN-1) 32V & 58V

**Bussmann**

**NEW**

Bussmann multi-pole fuses (MPF) are cartridge fuses containing three fuse elements of the same or differing ampere ratings for protecting three circuits with a single design. They are the OEM equivalent to the fuses used on popular Infiniti, Lexus, Nissan and Toyota vehicles manufactured since 2002.

Part Number	Ampere Ratings	Voltage	Colour Code
MPF-433X	40A + 30A + 30A	32VDC	Pink
MPF-444X	40A + 40A + 40A	32VDC	Green
MPF-533X	50A + 30A + 30A	32VDC	Red
MPF-534X	50A + 30A + 40A	32VDC	Blue
MPF-633X	60A + 30A + 30A	32VDC	Yellow
MPF2-324X	30A + 20A + 40A	58VDC	Yellow
MPF2-433X	40A + 30A + 30A	58VDC	Pink
MPF2-444X	40A + 40A + 40A	58VDC	Green
MPF2-533X	50A + 30A + 30A	58VDC	Red
MPF2-534X	50A + 30A + 40A	58VDC	Blue
MPF2-535X	50A + 30A + 50A	58VDC	Black
MPF2-555X	50A + 50A + 50A	58VDC	Maroon





**MPF (32VDC)**  
32.6 x 15.6 x 28mm  
(L x W x H)



**MPF2 (58VDC)**  
28.5 x 16 x 16mm  
(L x W x H)

FUSES + KITS

**Voltage:** See table  
**I.R.:** 1000A at rated voltage  
**Element:** Copper Alloy  
**Feature:** Element Window  
**Housing Flammability:** UL 94  
**Pack Size:** Varies, please contact sales.  
**Approvals:** ISO8820-4, JASO D612-4 RoHS



# FUSE STRIP LUG TYPE WITHOUT HOUSING 36V


**MTA**

Part Number	Ampere Rating
FBM030	30A
FBM040	40A*
FBM050	50A
FBM060	60A*
FBM070	70A*
FBM080	80A
FBM100	100A
FBM125	125A*
FBM150	150A*

90° Fork Type Lugs



**Voltage:** 36VDC **I.R.:** 625A  
**Material:** Zinc **Mounting:** M5 studs.  
**Holders:** In-Line Holder & Blocks (Midi fuse type)  
**Pack Size:** 10, 100, 2000  
**Notes:** Can be replaced by Midi fuse 58V M5 (see p.24)  
**Approvals:** DIN 72581/2 \*Not DIN standard. RoHS



Dimensions in MM

# FUSE STRIP RING TYPE WITHOUT HOUSING 32V

**Littelfuse**

Original equipment fuses suitable for older model Volkswagen, Audi, Seat, Skoda cars.


**NEW**

Part Number	Assortment Pack Contains 8pcs
0094040ZP	30A, 40A, 50A, 60A, 80A, 110A, 150A, 175A

**Voltage:** 32VDC **I.R.:** 1000A  
**Material:** Zinc Alloy **Mounting:** M6 studs.  
**Notes:** Can be replaced by Midi fuse 58V M6 (see p.24)  
**Approvals:** DIN 72581/2 RoHS



Assortment Pack



Dimensions in MM



**PROLEC**

Email: info@prolecproducts.com.au  
 Web: www.prolecproducts.com.au