

CIRCUIT BREAKERS - SERIES 17 PANEL MT



Features:

- Ignition protected and weatherproof.
- Standard or 90 degree stud orientation.
- Robust thermoplastic case.
- Corrosion resistant studs & hardware.
- Largest amperage range available.
- 1/4" or 3/8" stainless steel stud options.
- Superior moisture seal.
- Breaker made in USA. Bracket made in AU.

Auto Reset Type T1 1/4" Studs 3/8" Studs ^

Manual Reset Type T111 PTT 1/4" Studs 3/8" Studs ^

Part Number	Part Number	Ampere Rating
I71-P0-025	175-P0-025	25A
I71-P0-030	175-P0-030	30A
I71-P0-035	175-P0-035	35A
I71-P0-040	175-P0-040	40A
I71-P0-050	175-P0-050	50A
I71-P0-060	175-P0-060	60A
I71-P0-070	175-P0-070	70A
I71-P0-080	175-P0-080	80A
I71-P0-090	175-P0-090	90A
I71-P0-100	175-P0-100	100A
I71-P0-110	175-P0-110	110A
I71-P0-120	175-P0-120	120A
I71-P0-135	175-P0-135	135A
I71-P0-150	175-P0-150	150A
I71-P0-175	175-P0-175	175A
I71-P0-200	175-P0-200	200A
I71-P2-225 ^	175-P2-225 ^	225A NEW
I71-P2-250 ^	174-P2-250 ^*	250A NEW
I71-P2-275 ^	-	275A NEW
I71-P2-300 ^	-	300A NEW

(^ 3/8" Stud only) * Not PTT - (Push To Trip) Manual reset only.

I.R. Ratings:

- Type T1 (25A-150A): 3kA at 30VDC.
- Type T1 (175A-200A): 1.5kA at 30VDC.
- Type T1 (225A-300A): 2.5kA at 14VDC.
- Type T111 (25A-150A): 2.5kA at 14VDC, 1.5kA at 48VDC.
- Type T111 (175A-200A): 2.5kA at 14VDC, 1.5kA at 30VDC.
- Type T111 (225A-250A): 1.5kA at 14VDC.

Voltage Ratings:

- Type T1: (25A-200A): 30VDC, (225A-300A): 14VDC.
- Type T111: (25A-150A): 48VDC, (175A-200A): 30VDC.
- Type T111: (225A-250A): 14VDC.

Pack Size: Stock lines 1pc, indent items 9pcs.

Housing: UL 94-V0 rated black thermoplastic.

Termination: 1/4" or 3/8" Stainless steel studs.

Terminal Hardware: Stainless steel Sems nuts included.

Operating Temp: -40°C to 85°C. **Ingress Protection Rating:** IP67

Indicator: Bright yellow colour reset mechanism provides visual indication of tripped condition on manual reset breakers (T111).

Options: 90 Degree position studs suit horizontal busbar.

(I7x-P1 Series is an indent item only)


Approvals: SAE J1625, J1171, ABYC E-11, MIL-STD-202, UL I077 Ⓢ



Right Angle Mounting Bracket

Part Number: PROBRK017

Material: Stainless Steel



Auto Reset Type I Std. Orientation



Manual Reset Type III w/PTT Std. Orientation



Rear View 1/4" Studs Std. Orientation



Rear View 3/8" Studs Std. Orientation



Gasket Accessory

Part Number: B156-7003-J

Material: Black Santoprene.



Dimensions in MM

