

SPLASH PROOF CIRCUIT BREAKER KIT

Features:

- Includes Single Pole, Manual Reset (Type III) thermal circuit breaker.
- Includes Clear Cover for IP64 water resistance.
- Includes Terminal Boot to protect terminals from accidental shorts.
- Parallel mounting bracket.

| Part Number | Ampere Rating |
|-------------|---------------|
| CB3K-10 | 10A |
| CB3K-15 | 15A |
| CB3K-20 | 20A |
| CB3K-25 | 25A |
| CB3K-30 | 30A |
| CB3K-40 | 40A |
| CB3K-50 | 50A |

Voltage: 12-24VDC (Type III, manual reset).

I.R.: 2.5kA @ 12VDC.

Operating Temp: -10°C to 60°C

Body Type: Plastic case.

Features: Ignition Protected

Ingress Protection Rating: IP66 (excludes terminations).

Reset Overload Capacity: 6 x rated current.

Pack Size: 1 pc.

Mounting Hole: Bracket mounting holes 5.8 mm diameter.

Notes: Keys lock nuts included with circuit breakers.

Approvals: SAE J553, J1171 RoHS

Notes: When covers fitted, complies with ABYC E-9, USCG 33pl & ISO 10133. Terminal boot cable entry suits 18-10AWG cable.




Manual Reset Circuit Breaker

Push button to reset





Clear Cover Fitted

Parallel Bracket




Dimensions in MM



Terminal Specs
2 x #10-32 studs

Factory Logo →
Amperage & Voltage →
Part No. & Batch Code →

Product markings are laser etched.



Connect the short stud to battery (+), connect the long stud to auxiliary circuit(s).