



LIFT TRUCK FUSE BLOCK

Bussmann

Part Number
FBTB-LN

Rating: 800A
Voltage: 125VAC, 80VDC
Studs: 5/16" - 24
Hardware: Includes nylon insert lock nuts.
Base: Thermoplastic
Pack Size: 1
Notes: Countersunk mounting holes to suit No. 10 flat head screws. Fuses not included.
Suits Fuse: ANL, ANN and FBT series.



RELATED PRODUCTS:



FBT Fuses
Page 29



ANL Fuses
Page 29



ANN Fuses
Page 29

MARINE RATED BATTERY FUSE BAR ISOLATED STUD

Bussmann

- Suitable for DC Main, inverter, windlass and bow thruster circuit protection.
- Mounts on a M10 (3/8") battery post, battery switch or busbar.
- Provides high current protection in tight space constraints.
- Weatherproof, suitable for small locations & other harsh environments.
- Simple, economical and compact circuit protection system. Satisfies ABYC 7.
- Santoprene red or black insulating cap prevents accidental shorts.

Part Number	Description	Stud	Cover
CFBAR1M8SPRK	Single pole kit	M8	Red
CFBAR1M8SPBK	Single pole kit	M8	Black
CFBAR2M8SPRK	Double pole kit	M8	Red NEW
CFBAR2M8SPBK	Double pole kit	M8	Black NEW




CFBAR1 BLACK KIT
Single Pole Kit



CFBAR2 RED KIT
Double Pole Kit

Rating: 300A max per CFBAR
Voltage: 58VDC
Body: Thermoplastic PPS UL94-V0
Busbar: Nickel plated copper
Fuse Bar Stud: Stainless steel 1/4" -20 or M8.
Kit Contents: Includes S/S nuts, washers and cover.
Mounting: Mounts on a M10 (3/8") battery post. Optional M12 (1/2") version.
Suits Fuse: MRBF (Marine Rated Battery Fuse).
Notes: The updated 'SP' version of the battery fuse bar does not require a special isolating nut so regular nuts and washers can be fitted to the stud(s). Fuses not included.



Isolated Base

RELATED PRODUCTS:



MRBF fuses
Page 27



Scan this QR Code for more information



QR Code: 3000

HOLDERS