


Fast Acting Part Number	Slow Acting Part Number	Ampere Rating
515.100R	-	100mA
515.125R	515DA.125R	125mA
515.250R	515DA.250R	250mA
515.375	515DA.375R	375mA
515.500R	515DA.500R	500mA
515.750R	515DA.750R	750mA
-	515DA001R	1A
51501.5R	515DA01.5R	1.5A
515002R	515DA002R	2A
51502.5R	515DA02.5R	2.5A
515003R	515DA003R	3A
51503.5R	515DA03.5R	3.5A
515004R	515DA004R	4A
515005R	515DA005R	5A
515006R	-	6A
515007R	-	7A



Dimensions in MM



Custom made pigtail fuse versions also available.
Contact sales for further information.

Fast Acting

Voltage: 250VAC (100mA to 5A),
125VAC (6A to 7A)
VDC Contact sales.

Pack Size (bag): 10, 100.

Holders: Clips.

Axial Leaded Version: Also available in pigtail version (loose, tape and reel format). Custom order.
Contact sales for further information.

Imperial Dimensions: 0.59" x 0.2"

Approvals Available: Optional

Slow Acting

Voltage: 250VAC (125mA to 3A),
125VAC (3.5A to 7A)
VDC Contact sales.

Pack Size (bag): 10, 100.

Holders: Clips.


Axial Leaded Version: Also available in pigtail version (loose, tape and reel format). Custom order.
Contact sales for further information.

Imperial Dimensions: 0.59" x 0.2"

Approvals Available: Optional

Value Added Options

- Axial Lead Assembly
- Cut and Formed Leads
- Heat Shrink Insulating Sleeving
- Preassembled Fuses in Clips
- Tape & Reel Packaging
- Retail Clam Shell Packaging
- Retail Counter Stands
- Trade Assortment Kits



Contact sales for further information on the these value added options