


3AB SEMICONDUCTOR FUSES 1000VAC / 1000VDC



Part Number	Ampere Rating
3AB-FF.100/1000V	100mA
3AB-FF.125/1000V	125mA
3AB-FF.160/1000V	160mA
3AB-FF.200/1000V	200mA
3AB-FF.250/1000V	250mA
3AB-FF.315/1000V	315mA
3AB-FF.400/1000V	400mA
3AB-FF.500/1000V	500mA
3AB-FF.630/1000V	630mA
3AB-FF.800/1000V	800mA
3AB-FF001/1000V	1A
3AB-FF01.6/1000V	1.6A
3AB-FF002/1000V*	2A



Dimensions in MM

I.R.: 30kA at 1000VAC/VDC (100mA to 2A)

Voltage: 1000VAC / 1000VDC

Characteristic: Type aR, Very Fast Acting

Pack Size (bag): Stock lines 10

Pack Size (bag): Indent items 100


Holders: Clips (p112-113)

Approvals: c US

3AB SEMICONDUCTOR FUSES 500V - 250V



Part Number	Ampere Rating	Voltage AC
3AB-FF01.6	1.6A	500V
3AB-FF002	2A	500V
3AB-FF02.5	2.5A	500V
3AB-FF3.15	3.15A	500V
3AB-FF004	4A	500V
3AB-FF005	5A	500V
3AB-FF06.3	6.3A	500V
3AB-FF008	8A	500V
3AB-FF010	10A	500V
3AB-FF12.5	12.5A	500V
3AB-FF016	16A	500V
3AB-FF020	20A	250V
3AB-FF025	25A	250V



Dimensions in MM

I.R.: 1.5kA at 500VAC (1.6A to 16A)
TBC (20A to 25A)

Voltage: 500VAC (1.6A to 16A)
250VAC (20A to 25A)

Characteristic: Type aR, Very Fast Acting

Pack Size (bag): Stock lines 10

Pack Size (bag): Indent items 100

Holders: Clips (p112-113)

Approvals: