



Part Number	Ampere Rating	Body Size	Total I ² t at 660V	Voltage IEC / UL
I70M3458	40A	0/1*	270	690V / 700V
I70M3459	50A	0/1*	515	690V / 700V
I70M3460	63A	0/1*	770	690V / 700V
I70M3461	80A	0/1*	1 250	690V / 700V
I70M3462	100A	0/1*	2 450	690V / 700V
I70M3463	125A	0/1*	3 700	690V / 700V
I70M3464	160A	0/1*	7 500	690V / 700V
I70M3465	200A	0/1*	15 000	690V / 700V
I70M3466	250A	0/1*	28 500	690V / 700V
I70M3467	315A	0/1*	46 500	690V / 700V
I70M3468	350A	0/1*	68 500	690V / 700V
I70M3469	400A	0/1*	105 000	690V / 700V
I70M3470	450A	0/1*	140 000	690V / 700V
I70M3471	500A	0/1*	180 000	690V / 700V
I70M3472	550A	0/1*	230 000	690V / 700V
I70M3473	630A	0/1*	325 000	690V / 700V



Trigger Indicator & Microswitch Adapter



I70M4458	200A	1	11 500	690V / 700V
I70M4459	250A	1	21 000	690V / 700V
I70M4460	315A	1	42 000	690V / 700V
I70M4461	350A	1	59 000	690V / 700V
I70M4462	400A	1	91 500	690V / 700V
I70M4463	450A	1	120 000	690V / 700V
I70M4464	500A	1	170 000	690V / 700V
I70M4465	550A	1	230 000	690V / 700V
I70M4466	630A	1	350 000	690V / 700V
I70M4467	700A	1	465 000	690V / 700V
I70M4468	800A	1	725 000	690V / 700V
I70M4469	900A	1	850 000	550V / 700V

Body Size	Dimensions in MM						
	A	B	D	E	F	G	H
0/1*	50	51	59	45	M8	5	17
1	50	51	69	53	M8	8	20
2	50	51	77	61	M10	10	24
3	51	53	92	76	M12	10	30

I70M5458	400A	2	74 000	690V / 700V
I70M5459	450A	2	105 000	690V / 700V
I70M5460	500A	2	145 000	690V / 700V
I70M5461	550A	2	190 000	690V / 700V
I70M5462	630A	2	275 000	690V / 700V
I70M5463	700A	2	405 000	690V / 700V
I70M5464	800A	2	575 000	690V / 700V
I70M5465	900A	2	840 000	690V / 700V
I70M5466	1000A	2	1 250 000	690V / 700V
I70M5467	1100A	2	1 600 000	690V / 700V
I70M5468	1250A	2	2 400 000	690V / 700V



Fuse base with fuse fitted. #B301232

I70M6458	500A	3	95 000	690V / 700V
I70M6459	550A	3	135 000	690V / 700V
I70M6460	630A	3	210 000	690V / 700V
I70M6461	700A	3	300 000	690V / 700V
I70M6462	800A	3	465 000	690V / 700V
I70M6463	900A	3	670 000	690V / 700V
I70M6464	1000A	3	945 000	690V / 700V
I70M6465	1100A	3	1 300 000	690V / 700V
I70M6466	1250A	3	1 950 000	690V / 700V
I70M6467	1400A	3	2 450 000	690V / 700V
I70M6468	1500A	3	3 100 000	690V / 700V
I70M6469	1600A	3	3 900 000	690V / 700V
I70M6470	1800A	3	5 250 000	600V / 500V
I70M6471	2000A	3	6 350 000	550V / 500V



Accessory Microswitch Type K (Page I48)

I.R.: 200kA at rated voltage

Pack Size (box): 3

Microswitch (Type K): I70H0069 (pI48)

Holders: Sizes 0/1 & 1 (P/N: B301232). Sizes 2 & 3 (P/N: D301234).

Studs: Optional extra. Please contact sales.

Notes: Bussmann Body Size 1* = Size 0.

Approvals: IEC