

DIN 80		DIN 110		Ampere Rating	Body Size	Total I ² t at 660V
Part Number	Part Number					
170M3108	170M3258	40A	0/1*	270		
170M3109	170M3259	50A	0/1*	515		
170M3110	170M3260	63A	0/1*	770		
170M3111	170M3261	80A	0/1*	1 250		
170M3112	170M3262	100A	0/1*	2 450		
170M3113	170M3263	125A	0/1*	3 700		
170M3114	170M3264	160A	0/1*	7 500		
170M3115	170M3265	200A	0/1*	15 000		
170M3116	170M3266	250A	0/1*	28 500		
170M3117	170M3267	315A	0/1*	46 500		
170M3118	170M3268	350A	0/1*	68 500		
170M3119	170M3269	400A	0/1*	105 000		
170M3120	170M3270	450A	0/1*	140 000		
170M3121	170M3271	500A	0/1*	180 000		
170M3122	170M3272	550A	0/1*	230 000		
170M3123	170M3273	630A	0/1*	325 000		

170M4108	170M4258	200A	1	11 500
170M4109	170M4259	250A	1	21 000
170M4110	170M4260	315A	1	42 000
170M4111	170M4261	350A	1	59 000
170M4112	170M4262	400A	1	91 500
170M4113	170M4263	450A	1	120 000
170M4114	170M4264	500A	1	170 000
170M4115	170M4265	550A	1	230 000
170M4116	170M4266	630A	1	350 000
170M4117	170M4267	700A	1	465 000
170M4118	170M4268	800A	1	725 000
170M4119	170M4269	900A ^	1	850 000

170M5108	170M5258	400A	2	74 000
170M5109	170M5259	450A	2	105 000
170M5110	170M5260	500A	2	145 000
170M5111	170M5261	550A	2	190 000
170M5112	170M5262	630A	2	275 000
170M5113	170M5263	700A	2	405 000
170M5114	170M5264	800A	2	575 000
170M5115	170M5265	900A	2	840 000
170M5116	170M5266	1000A	2	1 250 000
170M5117	170M5267	1100A#	2	1 600 000
170M5118	170M5268	1250A#	2	2 400 000

170M6108	170M6258	500A	3	95 000
170M6109	170M6259	550A	3	135 000
170M6110	170M6260	630A	3	210 000
170M6111	170M6261	700A	3	300 000
170M6112	170M6262	800A	3	465 000
170M6113	170M6263	900A	3	670 000
170M6114	170M6264	1000A	3	945 000
170M6115	170M6265	1100A	3	1 300 000
170M6116	170M6266	1250A	3	1 950 000
170M6117	170M6267	1400A	3	2 450 000
170M6118	170M6268	1500A	3	3 100 000
170M6119	170M6269	1600A	3	3 900 000
170M6120	170M6270	1800A#	3	5 250 000
170M6121	170M6271	2000A ^	3	6 350 000

I.R.: 200kA at rated voltage

Voltage: 690VAC (IEC), 700VAC (UL)

Rated voltage 600V (IEC), ^ Rated voltage 550V (IEC).

Characteristic: Type aR, Very Fast Acting

Pack Size: 3 Holders; Blocks 170H.. (p137)

Microswitch (K Type): 170H0069 (p148)

Notes: Bussmann Body Size I* = Size 0. Approvals: DIN 43653 IEC



DIN 80



DIN 110



Fuses Fitted with Trigger Indicator and Microswitch Adaptor



Dimensions in MM

Body Size	DIN 80 Tag Type					
	A	B	C	D	E	H
0/1*	50	104	78	58	45	22
1	50	108	78	66	53	25
2	50	108	78	75	61	25
3	51	109	78	90	76	30

Body Size	DIN 110 Tag Type					
	A	B	C	D	E	H
0/1*	50	134	108	58	45	22
1	50	138	108	66	53	25
2	50	138	108	75	61	25
3	51	139	108	90	76	30