

NEOZED SEMICONDUCTOR FUSES 400V



Part Number	Ampere Rating	Total I ² t at 400VAC	Type / Size	Cap Diameter	Indicator Colour
NEO-FF002	2A	6.3	D01 / E14	7.3mm	Pink ●
NEO-FF004	4A	13	D01 / E14	7.3mm	Brown ●
NEO-FF006	6A	20	D01 / E14	7.3mm	Green ●
NEO-FF010	10A	65	D01 / E14	8.5mm	Red ●
NEO-FF016	16A	200	D01 / E14	9.7mm	Grey ●
NEO-FF020	20A	275	D02 / E18	10.9mm	Blue ●
NEO-FF025	25A	480	D02 / E18	12.1mm	Yellow ●
NEO-FF035	35A	1 000	D02 / E18	13.3mm	Black ●
NEO-FF050	50A	1 800	D02 / E18	14.5mm	White ○
NEO-FF063	63A	2 500	D02 / E18	15.9mm	Copper ●



I.R.: 50kA at 400VAC, 8kA at 250VDC

Voltage: 400VAC / 250VDC


Characteristic: Type gR, Very Fast Acting

Pack Size (box): 10, 25, 50

Features: Blown fuse visual indicator

Holders: Contact sales for further information.

Approvals: IEC







Dimensions in MM

BOTTLE SEMICONDUCTOR FUSES 500V



Part Number	Ampere Rating	Total I ² t at 500VAC	Type / Size	Cap Diameter	Indicator Colour
B16-FF002	2A	5.8	D1 / E16	6mm	Pink ●
B16-FF004	4A	11	D1 / E16	6mm	Brown ●
B16-FF006	6A	18	D1 / E16	6mm	Green ●
B16-FF010	10A	40	D1 / E16	8mm	Red ●
B16-FF016	16A	60	D1 / E16	10mm	Grey ●
B16-FF020	20A	139	D1 / E16	12mm	Blue ●
B16-FF025	25A	205	D1 / E16	14mm	Yellow ●
B27-FF002	2A	5.8	DII / E27	6mm	Pink ●
B27-FF004	4A	11	DII / E27	6mm	Brown ●
B27-FF006	6A	18	DII / E27	6mm	Green ●
B27-FF010	10A	40	DII / E27	8mm	Red ●
B27-FF016	16A	60	DII / E27	10mm	Grey ●
B27-FF020	20A	139	DII / E27	12mm	Blue ●
B27-FF025	25A	205	DII / E27	14mm	Yellow ●
B27-FF030	30A	310	DII / E27	14mm	Black ●
B33-FF035	35A	539	DIII / E33	16mm	Black ●
B33-FF050	50A	1 250	DIII / E33	18mm	White ○
B33-FF063	63A	1 890	DIII / E33	20mm	Copper ●



Dimensions in MM

Part Number	Ampere Rating	Total I ² t at 500VAC	Type / Size	Pin (A) Dia.	Base (B) Diam.
DIV-FF080	80A	4 200	DIV / R1 1/4"	5mm	33mm ○
DIV-FF100	100A	8 450	DIV / R1 1/4"	7mm	33mm ●
DV-FF125	125A	16 000	DV / R2"	5mm	46mm ●
DV-FF160	160A	24 000	DV / R2"	7mm	46mm ●
DV-FF200	200A	40 000	DV / R2"	9mm	46mm ●

I.R.: 50kA at 500VAC, 8kA at 315VDC

Voltage: 500VAC / 315VDC

Characteristic: Type gR, Very Fast Acting

Pack Size (box): 5, 10, 25, 50

Holders: Bases (p132)

Features: Blown fuse visual indicator

Approvals: IEC

