

SERVICE FUSE LINKS

Bussmann / Lawson
Fast Acting, Type gG

Part Number	Ampere Rating	Voltage (VAC)	I.R. at Rated VAC
LA-NB002	2A	240V	16.5kA
LA-NB005	5A	240V	16.5kA

LC-NB002	2A	240V	16.5kA
LC-NB005	5A	240V	16.5kA
LC-NB008	8A	240V	16.5kA
LC-NB010	10A	240V	16.5kA
LC-NB015	15A	240V	16.5kA
LC-NB020	20A	240V	16.5kA

LD-NB006	6A	240V	16.5kA
LD-NB010	10A	240V	16.5kA
LD-NB016	16A	240V	16.5kA
LD-NB020	20A	240V	16.5kA
LD-NB025	25A	240V	16.5kA
LD-NB030	30A	240V	16.5kA


MD-NB002	2A	415V	80kA*
MD-NB004	4A	415V	80kA*
MD-NB006	6A	415V	80kA*
MD-NB008	8A	415V	80kA*
MD-NB010	10A	415V	80kA*
MD-NB016	16A	415V	80kA*
MD-NB020	20A	415V	80kA*
MD-NB025	25A	415V	80kA*
MD-NB032	32A	415V	80kA*

I.R.: *Also rated 40kA at 250VDC

Pack Size (box): 10

Approvals (LA/LC/LD): BS1361

Approvals (MD): BS88-1, IEC60269-1



Dimensions in MM

SERVICE FUSE LINKS

Eaton Bussmann / Lawson
Fast Acting, Type gG

Part Number	Ampere Rating	Voltage (VAC)	I.R. at Rated VAC
LK-NB035	35A	240V	16.5kA
LK-NB040	40A	240V	16.5kA
LK-NB045	45A	240V	16.5kA


UK-NB045	45A	415V	TBA
UK-NB063	63A	415V	TBA

XK-NB063	63A	415V	TBA
XK-NB080	80A	415V	TBA
XK-NB100	100A	415V	TBA

Pack Size (box): 10

Approvals (LK): BS88 (35A-40A), BS1361, ASTA(45A)

Approvals (UK / XK): BS1361



Dimensions in MM