


14.3 x 51MM CARTRIDGE FUSES

dF / ETI
Fast & Slow Acting

Fast Acting Type gG/gL Part Number	Slow Acting Type aM Part Number	Ampere Rating
-	CH14-SB.250	250mA
-	CH14-SB.500	500mA
CH14-NB001	CH14-SB001	1A
CH14-NB002	CH14-SB002	2A
CH14-NB004	CH14-SB004	4A
CH14-NB006	CH14-SB006	6A
CH14-NB008	CH14-SB008	8A
CH14-NB010	CH14-SB010	10A
CH14-NB012	CH14-SB012	12A
CH14-NB016	CH14-SB016	16A
CH14-NB020	CH14-SB020	20A
CH14-NB025	CH14-SB025	25A
CH14-NB032	CH14-SB032	32A
CH14-NB040	CH14-SB040	40A
CH14-NB045*	CH14-SB045	45A
CH14-NB050	CH14-SB050	50A
CH14-NB055*	-	55A



Striker pin option.



Dimensions in MM

Fast Acting Type gG/gL I.R.: 100kA at 690VAC (1A to 25A)
120kA at 500VAC (32A & 40A)
120kA at 400VAC (50A)
20kA at 440VAC (45A & 55A)
Voltage: 690VAC (1A to 25A)
500VAC (32A, 40A & 50A)
440VAC (45A & 55A)

Slow Acting Type aM I.R.: 80kA at 690VAC (250mA to 25A)
120kA at 690VAC (32A)
120kA at 400VAC (40 to 50A)
Voltage: 690VAC (250mA to 25A)
500VAC (32A to 45A)
400VAC (50A)

Pack Size (box): 10

Holders: Clips (Call), Carriers (p127), Blocks (p133)

Option: Ratings 1A to 50A also available with inbuilt striker pin. Add 'P' to part number. Contact sales for further information.

Notes: *Contact sales for information on these ratings.

Approvals: IEC


22.2 x 58MM CARTRIDGE FUSES

dF / ETI
Fast & Slow Acting

Fast Acting Type gG/gL Part Number	Slow Acting Type aM Part Number	Ampere Rating
CH22-NB002	CH22-SB002	2A
CH22-NB004	CH22-SB004	4A
CH22-NB006	CH22-SB006	6A
CH22-NB008	CH22-SB008	8A
CH22-NB010	CH22-SB010	10A
CH22-NB012	CH22-SB012	12A
CH22-NB016	CH22-SB016	16A
CH22-NB020	CH22-SB020	20A
CH22-NB025	CH22-SB025	25A
CH22-NB032	CH22-SB032	32A
CH22-NB040	CH22-SB040	40A
CH22-NB050	CH22-SB050	50A
CH22-NB063	CH22-SB063	63A
CH22-NB080	CH22-SB080	80A
CH22-NB100	CH22-SB100	100A
CH22-NB125*	CH22-SB125*	125A



Striker pin option.



Dimensions in MM

Fast Acting Type gG/gL I.R.: 80kA at 690VAC (2A to 63A)
120kA at 500VAC (80A to 100A)
120kA at 400VAC (125A)
Voltage: 690VAC (2A to 63A)
500VAC (80A to 100A)
400VAC (125A)

Slow Acting Type aM I.R.: 80kA at 690VAC (2A to 63A)
120kA at 500VAC (80A to 100A)
120kA at 400VAC (125A)
Voltage: 690VAC (2A to 63A)
500VAC (80A to 100A)
400VAC (125A)

Pack Size (box): 10

Holders: Carriers (p127), Blocks (p133)

Option: Ratings 4A to 125A also available with inbuilt striker pin. Add 'P' to part number. Contact sales for further information.

Notes: *Overrating fuses

Approvals: IEC