
## PCB MOUNT AXIAL LEAD FUSES FAST & SLOW ACTING 125V



Fast Acting (F)	Time Delay (T)	Ampere
Part Number	Part Number	Rating
MQ.100	-	I00mA
MQ.125	-	I25mA
MQ.150	-	I50mA
MQ.200	-	200mA
MQ.250	MS.250	250mA
MQ.300	MS.300	300mA
MQ.375	MS.375	375mA
MQ.500	MS.500	500mA
MQ.750	MS.750	750mA
MQ001	MS001	IA
-	MS1.25	1.25A
MQ01.5	MS01.5	1.5A
MQ002	MS002	2A
MQ02.5	MS02.5	2.5A
MQ003	MS003	3A
MQ03.5	MS03.5	3.5A
MQ004	MS004	4A
MQ005	MS005	5A
MQ007	MS007	7A
MQ010	-	I0A
MQ012	-	I2A
MQ015	-	I5A



MS Wire Diameter: 0.81 mm (All ratings) Sample P/N: MQ002 for a 2A fuse.

Notes: End of life. Approvals: ( c RoHS

### PCB MOUNT AXIAL LEAD FUSES FAST ACTING 125V

**Littelfuse** 

#### Littelfuse 0251 Series


I.R.: 300A at rated VDC, 50A at rated VAC Voltage: 62mA to 10A Rated at 125VAC/VDC 12A to 15A Rated at 32VAC/VDC

Ratings (20) 62mA - 15A

Wire Diameter: 0.64mm (10A or less), 0.81mm (above 10A)

Sample P/N: 0251004 for a 4A fuse. Pack Size: Mixed packs, please contact sales

Approvals\*: SN (P) (R QPL TÜV (C) ROHS



Dimensions in MM

## PCB MOUNT AXIAL LEAD FUSES VERY FAST ACTING 250V



#### Littelfuse 0263 Series


I.R.: 50A at 250VAC, (PSE approval: 100A at 125VAC)

Voltage: 250VAC

Ratings (14): 62mA to 5A

Sample P/N: 0263003 for a 3A fuse. Pack Size: Mixed packs, please contact sales.

Approvals\*: St. (F) RoHS \*excludes some ratings.



# PCB MOUNT AXIAL LEAD FUSES SLOW ACTING 125V



#### Littelfuse 0473 Series

I.R.: 50A at 125VAC/VDC Voltage: 125VAC/VDC Ratings (13): 375mA to 7A Sample P/N: 0473005 for a 5A fuse. Pack Size: Mixed packs, please contact sales Notes: Meti (PSE) approval from IA to 5A only.

Approvals: SA ( P) ROHS



Swe-Check

Email: sales@swe-check.com.au Phone: (+61) 03 9521 6133