

## DIN NH-TYPE FUSES SIZE 2C / 2 (500V & 690V)



| 500VAC gG | Ampere Rating | Body Size |
|-----------|---------------|-----------|
| 2C-NB063  | 63A           | 2C        |
| 2C-NB080  | 80A           | 2C        |
| 2C-NB100  | 100A          | 2C        |
| 2C-NB125  | 125A          | 2C        |
| 2C-NB160  | 160A          | 2C        |
| 2C-NB200  | 200A          | 2C        |
| 2C-NB224  | 224A          | 2C        |
| 2C-NB250  | 250A          | 2C        |
| 2-NB300   | 300A          | 2         |
| 2-NB315   | 315A          | 2         |
| 2-NB355   | 355A          | 2         |
| 2-NB400   | 400A          | 2         |
| 2-NB425   | 425A          | 2         |
| 2-NB450   | 450A          | 2         |
| 2-NB500   | 500A*         | 2         |

| 690VAC gG | Ampere Rating | Body Size |
|-----------|---------------|-----------|
| 2C-GG063  | 63A           | 2C        |
| 2C-GG080  | 80A           | 2C        |
| 2C-GG100  | 100A          | 2C        |
| 2C-GG125  | 125A          | 2C        |
| 2C-GG160  | 160A          | 2C        |
| 2C-GG200  | 200A          | 2C        |
| 2C-GG224  | 224A          | 2C        |
| 2C-GG250  | 250A          | 2C        |
| 2-GG300   | 300A          | 2         |
| 2-GG315   | 315A          | 2         |
| -         | 355A          | -         |
| -         | 400A          | -         |
| -         | 500A          | -         |

| 690VAC aM | Ampere Rating | Body Size |
|-----------|---------------|-----------|
| 2C-AM063  | 63A           | 2C        |
| 2C-AM080  | 80A           | 2C        |
| 2C-AM100  | 100A          | 2C        |
| 2C-AM125  | 125A          | 2C        |
| 2C-AM160  | 160A          | 2C        |
| 2C-AM200  | 200A          | 2C        |
| 2C-AM224  | 224A          | 2C        |
| 2C-AM250  | 250A          | 2C        |
| -         | 300A          | -         |
| 2-AM315   | 315A          | 2         |
| 2-AM355   | 355A          | 2         |
| 2-AM400   | 400A          | 2         |
| -         | 500A          | -         |

**I.R. 500V:** 120kA at 500VAC (Type gG/gL)  
**I.R. 440V:** 120kA at 440VAC (Type gG/gL)\*  
**I.R. 690V:** 100kA at 690VAC (Type gG/gL/aM)  
**Voltage:** VAC as rated.

VDC call for confirmation.

**Pack Size (box):** 3



**Holders:** Bases (p139),

Disconnect Switches (p142-143)

**Accessories:** NH-Extractor (p150)

**Approvals:** IEC60269, DIN 43620, VDE 0636

**Notes:** gL (general application-normal acting).  
 aM (motor start-delayed action).



Dimensions in MM

| Size | A   | B  | C  | D  | E  |
|------|-----|----|----|----|----|
| 2C   | 150 | 72 | 73 | 46 | 20 |
| 2    | 150 | 72 | 73 | 54 | 25 |



## DIN NH-TYPE FUSES SIZE 3C / 3 (500V & 690V)



| 500VAC gG | Ampere Rating | Body Size |
|-----------|---------------|-----------|
| 3C-NB250  | 250A          | 3C        |
| 3C-NB315  | 315A          | 3C        |
| 3C-NB355  | 355A          | 3C        |
| 3C-NB400  | 400A          | 3C        |
| 3-NB425   | 425A          | 3         |
| 3-NB500   | 500A          | 3         |
| 3-NB560   | 560A          | 3         |
| 3-NB630   | 630A          | 3         |
| 3-NB800   | 800A*         | 3         |

| 690VAC gG | Ampere Rating | Body Size |
|-----------|---------------|-----------|
| 3C-GG250  | 250A          | 3C        |
| 3C-GG315  | 315A          | 3C        |
| 3-GG355   | 355A          | 3         |
| 3-GG400   | 400A          | 3         |
| 3-GG425   | 425A          | 3         |
| 3-GG500   | 500A          | 3         |
| -         | 560A          | -         |
| -         | 630A          | -         |
| -         | 800A          | -         |

| 690VAC aM | Ampere Rating | Body Size |
|-----------|---------------|-----------|
| 3-AM315   | 315A          | 3         |
| 3-AM355   | 355A          | 3         |
| 3-AM400   | 400A          | 3         |
| 3-AM425   | 425A          | 3         |
| 3-AM500   | 500A          | 3         |
| -         | 560A          | -         |
| -         | 630A          | -         |
| -         | 800A          | -         |

**I.R. 500V:** 120kA at 500VAC (Type gG/gL/aM)  
**I.R. 440V:** 120kA at 440VAC (Type gG/gL)\*  
**I.R. 690V:** 100kA at 690VAC (Type gG/gL/aM)  
**Voltage:** VAC as rated. VDC call for confirmation.

**Pack Size (box):** 3

**Holders:** Bases (p139), Disconnect Switches (p142-143)

**Accessories:** NH-Extractor (p150)

**Approvals:** IEC60269, DIN 43620, VDE 0636

**Notes:** gL (general application-normal acting).  
 aM (motor start-delayed action).

Dimensions in MM

| Size | A   | B  | C  | D  | E  |
|------|-----|----|----|----|----|
| 3C   | 150 | 72 | 84 | 54 | 25 |
| 3    | 150 | 72 | 84 | 65 | 32 |

