## **POWER DIST. MODULE SEALED - 6 POSITION**







NEW

terminals with 2.8mm blades on 8.1mm centerline spacing. This PDM is compact, durable and sealed power distribution unit. Simply

The HWB6 series is a DC power distribution box that can hold 3 plug in circuit protection components eg. Mini blade fuses (32V or 58V), Mini blade diodes or Mini circuit breakers. These components feature

connect a power input and power output cable to each component. Parts can be ordered separately or in a kit as described below. Plug-in components eg. Mini fuses, mini blade circuit breakers are not included and can be ordered separately.

Voltage Rating: 58VDC

Maximum Continuous Current: 72A (30A Per Circuit

Maximum Fuse Rating: 30A per circuit. Temperature Rating: -40°C to +85°C. Housing: PA66 GF30, Black, UL 94 V-0

Cover: Clear UL94 V-2 Cover Seal: Silicone, green.

Cover must be oriented correctly in order to secure yellow tabs.

Mounting Bracket: Plated steel - straight (standard).

Wire Size: #22 - #13 AWG (0.35 to 2.5mm<sup>2</sup>).

Ingress Protection Rating: IP67 / IP69K when cover, cable seals & cavity plugs are installed. Cavity plugs must be installed in any empty positions. Cable Seals: Please check the overall diameter of your cable before

ordering cable seals.

Terminals: Tyco AMP MCP 2.8, Female Copper Nickel / Tin Plated.

Terminal Capacity: 6 terminals.

Terminal Tools: Terminal crimping & removal tools refer page 185-186. Options: 30 deg. angled mounting bracket, black cover & cover tether.

Part Number	Kit Contents

PDMKIT321 PDM Module, Clear Cover, Straight Bracket, I x TPA, 6 x Terminals (1-968876-1), 6 x Cable Seals (828905-1).

Part Number Description PDM32003ZXM

PDM Module, Clear Cover, Straight Bracket, 3 x TPA's. PDM32004ZXM PDM Module, Black Cover, Straight Bracket, 3 x TPA's. 1-968875-1 Terminal Female (#20 - #16AWG), 0.5 - 1.0mm<sup>2</sup> I-968876-I Terminal Female (#16 - #14AWG), 1.5 - 2.5mm2 828904-I Cable Seal Blue Silicone. 1.2 - 2. 1 mm Cable Dia. 828905-1 Cable Seal White Silicone, 2.2 - 3.0mm Cable Dia. 828922-I Cavity Plug Clear Silicone, 5.6mm Cavity inside Dia.

868-068 Angled Bracket 30 Degree (optional).

Cover Tether (optional). 890009470





**Fuses Not Included** 



PDMKIT321 (Kit)

Page: 1

## RELATED PRODUCTS:



**Mini Type Devices** 








Fuse & Breaker Puller

Email: info@prolecproducts.com Datasheet: 9050 Web: www.prolecproducts.com

## **Dimensions**







 $Dimensions \ in \ MM$