MINI RELAY SEALED CONNECTOR (4 OR 5 PIN)

The Series PTSR-X Push-to-Seat sealed relay connector is specifically designed to accept standard Mini ISO skirted relays, Delphi 630 Metri-Pack terminals and 480 Metri-Pack seals. This uniquely designed sealed unit features a Push-to-Seat connection system. Terminals are crimped to cable, then pushed into base of unit. This eliminates the costly labor intensive "5 step" pull-to-seat assembly approach required by other connectors.

Features:

- Sealed, Ingress Protection Rated IP66.
- Labor saving "Push to Seat" connection system.
- Molded in rugged polyester thermoplastic material.
- Finger release latch.
- Accepts any wire size, in any cavity using Aptive 630 Metri-Pack
- sealed push to seat terminals together with 480 Metri-Pack seals.

Kit Contents; Part Number PTSR-KIT I x Connector with Seal Assembly I x Blue TPA Term, Pos, Assurance 2 x Terminals (20-18AWG) 2 x Yellow Seals (18AWG) 3 x Terminals (12-10AWG) 3 x Orange Seals (10AWG) I x Cavity Plug Grey

onnector Kit

with skirted mini ISO relay.

Dent Niemele en	Description
Part Number	Description
PTSR-A	Connector with Red Silicon Seal Assembly.
PTSR-T	Terminal Position Assurance (TPA) Blue Nylon.
53 733	Terminal Female Sealed Tin (10 AWG) $4.0 - 6.0$ mm ²
12052456	Terminal Female Sealed Tin (12-10AWG) 3.0 - 5.0mm ²
12052455	Terminal Female Sealed Tin (16-14AWG) 1.0 - 2.0mm ²
12052457	Terminal Female Sealed Tin (20-18AWG) 0.5 - 0.8mm ²
15324987	Cable Seal Orange (10AWG) 4.40 - 5.16mm Cable Dia.
15324990	Cable Seal Purple (12AWG) 3.61 - 4.50mm Cable Dia.
15324989	Cable Seal Red (14AWG) 2.81 - 3.76mm Cable Dia.
15324988	Cable Seal White (16AWG) 2.01 - 2.85mm Cable Dia.
15324991	Cable Seal Yellow (18AWG) 1.60 - 2.15mm Cable Dia.
35232480	Cavity Plug Grey 9.05mm Diameter




Voltage: 58VDC Base Material: Polyester thermoplastic Seal Material: Silicon TPA Material: Nylon Terminals: Tin Plated Brass Metri-Pack 630. Cable Seals & Cavity Plug: Silicone. Pack Size: 1, 10, 100, 500 Approvals: RoHS



Mini ISO Skirted Relay With Bracket 896HICHDISWR Series 12V and 24V SPDT (see p.167)









Dimensions in MM

40.8







PTSR-T

Terminals

ТРА

PTSR-A





22.5





Email: info@prolecproducts.com.au Web: www.prolecproducts.com.au