

INSULATED HEAT SHRINK BUTT SPLICE CONNECTORS

PROLEG

Perma-Seal splices provide a rugged, environmentally sealed connection for wire sizes that will insulate, seal and protect joints from physical abuse and abrasion, water, salt and other corrosive compounds.

Part Number	Connector	Wire Gauge	Colour	A (mm)	B (mm)	C (mm)
19164-0013	Butt Splice	22-18AWG	Red	15	39.4	4.7
19164-0044	Butt Splice	16-14AWG	Blue	15	39.4	4.95
19164-0056	Butt Splice	12-10AWG	Yellow	15	45.7	6.99



Voltage: Maximum 600V

Barrel Type: Closed

Material Plating - Mating & Termination: Tin

Material Metal: Copper **Insulation:** NiAc™

Temperature Range Operating: -55°C to +125°C

Wire Insulation Diameter: 5.97mm max.


Pack Size: 10, 50, 100, 500



1/. Insert both cables & crimp



2/. Apply heat to seal









MALE & FEMALE PVC INSULATED DISCONNECTS

MTA

NEW

Part Number	Nylon Insulated	Wire Section	L1 (mm)	L2 (mm)	Dia	Colour
1852000	1/4" Male Push On	0.25-1.00mm ²	12	21.0	1	Red
1856000	1/4" Male Push On	1.00-2.50mm ²	12	21.0	2	Blue
1862000	1/4" Male Push On	2.50-6.00mm ²	13	22.5	3	Yellow
1851500	1/4" Female Push On	0.25-1.00mm ²	-	23.5	4	Red
1855500	1/4" Female Push On	1.00-2.50mm ²	-	23.5	5	Blue
1860500	1/4" Female Push On	2.50-6.00mm ²	-	24.0	6	Yellow

RELATED PRODUCTS:



Crimping Tools
(see p.184)

TUBULAR TERMINAL CRIMPING TOOL


MTA

NEW

Part Number	Screw Hole	Wire Section	Dia.
05000BK	M6	16mm ²	1
05100BK	M8	16mm ²	1
05010BK	M8	25mm ²	2
05021BK	M8	35mm ²	2
05110BK	M10	25mm ²	3
05020BK	M10	35mm ²	3
05030BK	M11	50mm ²	4
05040BK	M13	75mm ²	5



RELATED PRODUCT:



Crimping Tool
(see p.184)

