## **INSULATED HEAT SHRINK BUTT SPLICE CONNECTORS**

Perma-Seal splices provide a rugged, environmentally sealed connection for wire sizes that will insulate, seal and protect joints from physical abuse and abrasion, water, salt and other corrosive compounds.

<u>Part Number</u> 19164-0013	<u>Connector</u> Butt Splice	<u>Wire Gauge</u> 22-18AWG	<u>Colour</u> Red	<u>A (mm)</u> 15	<u>B (mm)</u> 39.4	<u>C (mm)</u> 4.7
19164-0044	Butt Splice	16-14AWG	Blue	15	39.4	4.95
19164-0056	Butt Splice	12-10AWG	Yellow	15	45.7	6.99

Voltage: Maximum 600V Barrel Type: Closed Material Plating - Mating & Termination: Tin Material Metal: Copper Insulation: NiAc™ Temperature Range Operating: -55°C to +125°C Wire Insulation Diameter: 5.97mm max. Pack Size: 10, 50, 100, 500

## MALE & FEMALE PVC INSULATED DISCONNECTS


Part Number 1852000 1856000 1862000 1851500 1855500	Nylon Insulated 1/4" Male Push On 1/4" Male Push On 1/4" Male Push On 1/4" Female Push On 1/4" Female Push On		LI (mm) 12 12 13 -	L2 (mm) 21.0 21.0 22.5 23.5 23.5	<u>Dia</u> 1 2 3 4 5	Colour Red Blue Yellow Red Blue	NE
1855500 1860500	I/4" Female Push On I/4" Female Push On	1.00-2.50mm <sup>2</sup>			5	Blue Yellow	

I/. Insert both cables & crimp

HALLES DATE ALLESS

AND CO ACID AT

2/. Apply heat to seal



## **TUBULAR TERMINAL CRIMPING TOOL**

Part Number	Screw Hole	Wire Section	Dia.
05000BK	M6	16mm <sup>2</sup>	1
05100BK	M8	16mm <sup>2</sup>	1
05010BK	M8	25mm <sup>2</sup>	2
05021BK	M8	35mm <sup>2</sup>	2
05110BK	M10	25mm <sup>2</sup>	3
05020BK	MI0	35mm <sup>2</sup>	3
05030BK	MII	50mm <sup>2</sup>	4
05040BK	MI3	75mm <sup>2</sup>	5

## **RELATED PRODUCT:**










ั่ว8



Email: info@prolecproducts.com.au Web: www.prolecproducts.com.au



PROLEG





12

L2

NEW