

Applications include Battery chargers, trucks, buses, RVs, trolling motors, etc.
 Function options include Auto (TI), Manual (TIII) or optional Modified Reset Circuit (TII) Breakers.

IGNITION
 PROTECTED
IP66*



12VDC Automatic TI Plastic Cover Parallel Bracket



12VDC Manual TIII Plastic Cover Parallel Bracket



12VDC Automatic TI Metal Cover Parallel Bracket




12VDC Automatic TI Metal Cover Cross Bracket


| Part Number | Part Number | Part Number | Part Number | Ampere Rating |
|-------------|-------------|-------------|-------------|---------------|
| I21A05-B2P | I23A05-B2P | I21A05-B2M | I21A05-A2M | 5A |
| I21A08-B2P | I23A08-B2P | I21A08-B2M | I21A08-A2M | 8A |
| I21A10-B2P | I23A10-B2P | I21A10-B2M | I21A10-A2M | 10A |
| I21A15-B2P | I23A15-B2P | I21A15-B2M | I21A15-A2M | 15A |
| I21A20-B2P | I23A20-B2P | I21A20-B2M | I21A20-A2M | 20A |
| I21A25-B2P | I23A25-B2P | I21A25-B2M | I21A25-A2M | 25A |
| I21A30-B2P | I23A30-B2P | I21A30-B2M | I21A30-A2M | 30A |
| I21A35-B2P | I23A35-B2P | I21A35-B2M | I21A35-A2M | 35A |
| I21A40-B2P | I23A40-B2P | I21A40-B2M | I21A40-A2M | 40A |
| I21A50-B2P | I23A50-B2P | I21A50-B2M | I21A50-A2M | 50A |

Voltage: 14VDC (I21 Series), 28VDC (I23 & I24 series)
I.R.: 2.5kA @ 12VDC (Branch circuit protection). Contact sales for further info.
Operating Temperature: -40°C to 85°C.
Storage Temperature: -40°C to 125°C
Features: Ignition Protected
Ingress Protection Rating: IP66* (Plastic cover only, except terminals).
Pack Size: Stock lines 1pc, indent items 250pcs.
Mounting Hole: Bracket mounting holes 4.98 mm diameter.
Notes: Keys lock nuts included with circuit breakers.
Approvals: SAE J553, J1171


Terminal Specs:
 Two 10-32 studs




Plastic Cover Parallel Bracket




Metal Cover Parallel Bracket



Metal Cover Cross Bracket





Connect the short stud to battery (+), connect the long stud to auxiliary circuit(s).



RELATED PRODUCTS:

| Part Number | Description | NEW |
|-------------|-----------------------------|-------------------------------------|
| CBBP | Parallel TIII Clear Cover | <input type="checkbox"/> |
| CBBR | Red PVC Terminal Boot | <input checked="" type="checkbox"/> |
| CBBB2 | 2 Position Brass Tin Busbar | |
| CBBB3 | 3 Position Brass Tin Busbar | |
| CBBB4 | 4 Position Brass Tin Busbar | <input checked="" type="checkbox"/> |
| CBBB6 | 6 Position Brass Tin Busbar | |
| CBBB8 | 8 Position Brass Tin Busbar | <input checked="" type="checkbox"/> |



Notes: CBBP covers are IP64 water resistant. They protect the manual reset circuit breaker button against dust and water. The CBBR PVC boots protect terminal connections from accidental shorts. Use to comply with ABYC E-9, USCG 33pl & ISO 10133. Fits breakers with or without brackets. Both TI & TIII. Cable entry 18-10AWG. Busbars suitable for breakers fitted with a parallel bracket or without bracket.