

Typically used in DC power systems in marine applications (as a main or branch circuit breaker), truck and bus systems, RV systems, add-on protection for accessories, lift gates, etc.

IGNITION
PROTECTED
IP66

Features:

- Single lever for manual reset switching operations.
- Capable of withstanding 3000 on/off cycles at 48VDC.
- Ignition Protected and weatherproof.
- Corrosion resistive materials.
- Large clearance around studs to accept large gauge wire lugs.



Surface Mount Manual Reset TIII Switchable

Part Number	Amperage Rating
I87025F-03-I	25A
I87030F-03-I	30A
I87035F-03-I	35A
I87040F-03-I	40A
I87050F-03-I	50A
I87060F-03-I	60A
I87070F-03-I	70A
I87080F-03-I	80A
I87100F-03-I	100A
I87110F-03-I	110A
I87120F-03-I	120A
I87135F-03-I	135A
I87150F-03-I	150A
I87200F-03-I	200A

Panel Mount Manual Reset TIII Switchable

Part Number	Amperage Rating
I87025P-03-I	25A
I87030P-03-I	30A
I87035P-03-I	35A
I87040P-03-I	40A
I87050P-03-I	50A
I87060P-03-I	60A
I87070P-03-I	70A
I87080P-03-I	80A
I87100P-03-I	100A
I87110P-03-I	110A
I87120P-03-I	120A
I87135P-03-I	135A
I87150P-03-I	150A
I87200P-03-I	200A

Surface Mount Manual Reset



5/16" - 18 Threaded Studs

Voltage: 48VDC

I.R.: Main Breaker Protection.

5kA at 14VDC, 3kA at 28VDC, 1.5kA at 48VDC

Reset Mechanism: Type TIII, Manual reset & switchable.

Pack Size: Stock lines 1 pc, indent items 60 pcs.

Mounting Options: Surface or Panel Mount.

Operating Temp: -40°C to 85°C.

Storage Temp: -40°C to 125°C

Materials: Base UL-Rated 94V-0 thermoset plastic.

Cover & lever UL-Rated 94V-0 thermoplastic.

Marking: Standard marking includes amp/volt ratings.

Terminal Hardware: Stainless nuts & lock washers installed.

Termination: 5/16" - 18 threaded studs.

Torque Rating: 8.5Nm max.

Mounting Torque Rating: 5.6Nm max.

Ingress Protection Rating: IP66

Approvals: SAE J1171, ABYC E-11 CE

Panel Mount Manual Reset



NEW


Series 87.
Marine Rated
Circuit Breakers.
Panel or Surface Mount
48VDC
25A through to 250A.





Scan this
QR Code
for more
information

QR Code: 10004

Recommended Panel Mounting Cut-Out



Recessed Mounting Hole for #10 Screws



Dimensions in MM

5/16" - 18 Threaded Studs