MICRO2 FUSE BLOCKS LATERAL CONNECTION

Part Number	No. Po
FB4-ATR	4 Pole
FB6-ATR	6 Pole

o. Poles <u>Max Amps Per Block</u> Pole 30A Pole 45A

Voltage: 32V

Circuit Rating: 15A max per circuit Cover: Clear with o-ring seal Block: Moisture resistant back plate IP Rating: IPx4 (Splash proof) Terminals: Lateral 1/4" QC (6.25mm). Mounting: Surface mount, M5 screw. Pack Size: 1 Options: Also available in 8 & 10 way.

Notes: Fuses not included.

RELATED PRODUCTS:




Micro2 Fuses (see p.13)

FB4-ATR

83 (L) x 45 (W) x 39 (H) Fixing Centre (FC): 65mm

Mounting Diagram



FB6-ATR 103 (L) x 45 (W) x 39 (H) Fixing Centre (FC): 85mm

to secure fuse holder to vehicle.



ETON Bussmann

NEW

IPX4

MINI FUSE BLOCK AXIAL CONNECTION

Features:


- Up to 7 x Mini fuse protected circuits & space to store 3 x spare fuses.
- Compact design for mounting in tight spaces using cable ties.
- Kit includes plenty of terminals in 3 different sizes to suit a wide range of cable sizes.
- Hinged cover protects fuses from the elements. Inside legend identifies the circuits.

Part Number Kit Description 01435K Mini Fuse Block Kit Includes; 1 × 01430 (7 way frame) 7 × 01420 (Mini fuse modules) 16 × 08330BK (Bulk terminals 0 16 × 08331BK (Bulk terminals 0

16 x 08330BK (Bulk terminals 1 - 2 mm² 16A) 16 x 08331BK (Bulk terminals 1 - 2 mm² 16A) 16 x 08332BK (Bulk terminals 2.5 to 4mm² 28A)

Voltage: 32V Body: Black rubber (PA 66 GF30) Terminals: Tin plated copper Terminal Options: BK = Bulk Pack. Pack Size: 1, 400 Notes: Cable ties not supplied. Fuses not included. Approvals: RoHS

Fuse Housing






RELATED PRODUCTS:




Fuse Frame




Female Terminal









Email: info@prolecproducts.com.au Web: www.prolecproducts.com.au 

Storage for 3 spare fuses.

86