


The Littelfuse BF2 series fuse range is rated at 58V and offers a bolt-on fuse for high current wiring protection. The transparent housing allows for easy detection of blown fuses.

Part Number	Ampere Rating	Body Colour
MEG100-58V	100A	Yellow
MEG125-58V	125A	Green
MEG150-58V	150A	Orange
MEG175-58V	175A	White
MEG200-58V	200A	Blue
MEG225-58V	225A	Tan
MEG250-58V	250A	Pink
MEG300-58V	300A	Grey



Dimensions in MM



I.R.: 1kA at 58VDC

Voltage: 58VDC

Pack Size: 1, 10, 100

Holders: Inline, Blocks & Power Dist. Unit.

Mounting: M8 or 5/16" studs

Features: Window element.

Opaque Housing: PET-GF30

Clear Housing: PES

Terminal: Copper alloy, gal. Sn

Approvals: ISO 8820-5,
UL 248 Special Purpose Fuses



Time Characteristic % of Amp Rating	Opening Time (Min/Max)	
	100A - 250A	300A
75%	-/-	-/-
100%	4hrs/-	4hrs/-
135%	120sec/1800sec	-/-
200%	1sec/15sec	1sec/15 sec
350%	0.3sec/5sec	0.5sec/5sec
600%	0.1sec/1sec	0.1sec/1sec